

Microstrip Isolator 2.5GHz to 26.5GHz

- Good temperature behavior,high aseismatic capability.
- Low insertion loss,high power handling,high isolation.
- Meet RoHS standard, high quality,low price,fast delivery.
- Commercial, military and space applications.
- May according to demand making to order.
- One year standard limited warranty.



Part Number	Frequency Range (GHz)	Bandwidth Max. (MHz)	Insertion Loss Max.(dB)	Isolation Min. (dB)	VSWR Max.	FWD/REV Power (W)	Dimension L×W×H (mm)	Connector Type	Temp. Range (°C)
SS-MI1618A	2.5-3.5	500	0.6	18	1.4	20/3	16×18×10	Microstrip	-55~+85
SS-MI1416A	3.0-4.5	600	0.5	19	1.3	20/3	14×16×8	Microstrip	-55~+85
SS-MI1214A	4.0-5.5	800	0.5	19	1.3	15/3	12×14×8	Microstrip	-55~+85
SS-MI912A	5.0-7.0	800	0.5	19	1.3	15/2	9.5×12×5	Microstrip	-55~+85
SS-I910A	6.5-9.5	900	0.5	18	1.35	15/2	9×10×5	Microstrip	-55~+85
SS-MI67A	8-13	1600	0.5	19	1.3	15/2	6×7.5×5	Microstrip	-55~+85
		800	0.4	20	1.25				
	8-12	Full	0.5	14	1.35				
	12-18	1800	0.5	17	1.3				
	12-18	1200	0.5	20	1.25				
	18-26.5	1800	0.6	18	1.3				

* Please specifies frequency range and power when you put order.

* The narrower frequency range you choose, the higher performance and lower cost you can expect.

* If your requirement not in list, we still can make it, please contact us.