

## Drop-in Isolator 300 to 1900MHz

- Ø Good temperature behavior,high aseismatic capability.
- Ø Low insertion loss,high power handling,low IMD design.
- Ø Meet RoHS standard, high quality,low price,fast delivery.
- Ø Commercial, military and space applications.
- Ø May according to demand making to order.
- Ø One year standard limited warranty.

### Product Specifications:

| Part Number | Freq. Range (MHz) | Bandwidth Max. (MHz) | Insertion Loss Max.(dB) | Isolation Min. (dB) | VSWR Max. | FWD/REV Power (W) | Connector Type | Temp. Range (°C) |
|-------------|-------------------|----------------------|-------------------------|---------------------|-----------|-------------------|----------------|------------------|
| SS-DI3538A  | 300-400           | 20                   | 0.4                     | 20                  | 1.25      | 300/30            | Drop in        | -30~+70          |
|             | 400-600           | 30                   | 0.3                     | 23                  | 1.2       |                   |                |                  |
|             | 380-460           | Full                 | 0.5                     | 18                  | 1.3       |                   |                |                  |
|             | 500-1300          | 100                  | 0.4                     | 20                  | 1.25      |                   |                |                  |
|             | 700-1900          | 200                  | 0.5                     | 20                  | 1.25      |                   |                |                  |

\* Please specifies frequency range and power when you put order.

\* If your requirement not in list, we still can make it, please contact us.

### Outline Drawing (Unit: mm)

