Drop-in Isolator 240 to 1300MHz

- Good temperature behavior,high aseismatic capability.
- Low insertion loss,high power handling,low IMD design.
- Meet RoHS standard, high quality,low price,fast delivery.
- Commercial, military and space applications.
- May according to demand making to order.
- One year standard limited warranty.

Product Specifications:

Part Number	Freq. Range (MHz)	Bandwidth Max. (MHz)	Insertion Loss Max.(dB)	Isolation Min. (dB)	VSWR Max.	FWD/REV Power (W)	Connector Type	Temp. Range (℃)
SS-DI4550A	240-280	10	0.6	20	1.25	300/30	Drop in	-30~+70
	280-350	20	0.4	23	1.2			
	350-450	30	0.3	23	1.2			
	450-1300	100	0.3	23	1.2			
	690-1000	Full	0.7	17	1.3			
	700-1000	Full	0.6	18	1.3			

* Please specifies frequency range and power when you put order.
* If your requirement not in list, we still can make it, please contact us.

Outline Drawing (Unit: mm)



◇Tel: +86-755-88820302 ◇E-mail: sales@saisum.com ◇Web Site: www.saisum.com
◇Fax: +86-755-88820301 ◇Add: F/15,ITC Building,Southlake Road,Luohu District,Shenzhen,China.